



Contact 914 260 7821  
[frank@gemconequip.com](mailto:frank@gemconequip.com)

[www.gemindustriesusa.com](http://www.gemindustriesusa.com)

## HI - TIP BUCKET

- Available in a range of sizes from 0.75cy(5 ft) up to 1.1 cy(7 ft).
- Discharge height and forward reach increased.
- For use with various materials such as gravel, grain, woodchips, compost, etc.
- Soft close twin double acting hydraulic rams that are protected within double skin sides.
- Flat floor for easy loading, with 400 Brinell steel cutting edge.
- Can be fitted with optional 400 Brinell bolt on reversible cutting edge.
- High yield alloy steel used in the carriage frame for a longer working life.
- Designed with a low back for better vision and side access steps for safety.



### Technical Data

	HTBSS0.65	HTBSS 0.75	HTBSS 0.85
Height (IN)	29	29	29
Width (FT)	5 FT	6 FT	7 FT
Depth (IN)	54	54	54
Capacity (CY)	0.75	0.85	1.00
Weight (LB)	1056	1265	1408
Sides (IN)	5/16	5/16	5/16
Shell (IN)	1/4	1/4	1/4
Cutting edge(Ins)	6 X 3/4	6 X 3/4	6 X 3/4
Rams	2x75mm Bore	2x75mm Bore	2x75mm Bore